

# SPIR 1.2 Specification for OpenCL

Khronos Group - OpenCL Working Group - SPIR subgroup

2013-05-31

## Abstract

This document defines version 1.2 of the Standard Portable Intermediate Representation (SPIR) for OpenCL™.<sup>1</sup>

The Khronos Group Inc. ratified this document as a provisional specification on August 24, 2012.

## Contents

<b>1</b>	<b>Introduction</b>	<b>6</b>
1.1	One format, two notations . . . . .	6
1.2	Name mangling . . . . .	6
<b>2</b>	<b>OpenCL C mapping to SPIR</b>	<b>7</b>
2.1	Supported Data Types . . . . .	7
2.1.1	Built-in Scalar Data Types . . . . .	7
2.1.2	Built-in Vector Types . . . . .	7
2.1.3	Other Built-in Data Types . . . . .	8
2.1.3.1	Declaring sampler variables . . . . .	9
2.1.3.2	Image channel data type values . . . . .	9
2.1.3.3	Image channel order values . . . . .	10
2.1.3.4	Zero events . . . . .	10
2.1.3.5	NULL pointer . . . . .	10
2.1.4	Alignment of Types . . . . .	10
2.1.5	Structs . . . . .	10
2.2	Address space qualifiers . . . . .	10
2.3	Kernel qualifiers . . . . .	11
2.3.1	Optional attribute qualifiers . . . . .	12
2.3.1.1	Work group size information . . . . .	12
2.3.1.2	Vector type hint information . . . . .	12
2.4	Kernel Arg Info . . . . .	13
2.5	Storage class specifier . . . . .	14
2.6	Type qualifiers . . . . .	14
2.7	Attribute Qualifiers . . . . .	14
2.7.1	Type Attributes . . . . .	14
2.7.1.1	aligned attribute . . . . .	14
2.7.1.2	packed attribute . . . . .	14
2.7.2	Variable Attributes . . . . .	14
2.7.2.1	aligned attribute . . . . .	14

---

<sup>1</sup>OpenCL and the OpenCL logo are trademarks of Apple Inc.

2.8	Compiler Options . . . . .	15
2.9	Preprocessor Directives and Macros . . . . .	16
2.9.1	Preprocessor Directives . . . . .	16
2.9.2	Macros . . . . .	16
2.10	Built-ins . . . . .	16
2.10.1	Name Mangling . . . . .	16
2.10.2	Synchronization Functions . . . . .	16
2.10.3	The printf function . . . . .	17
2.11	KHR Extensions . . . . .	17
2.11.1	Declaration of used optional core features . . . . .	17
2.11.2	Declaration of used KHR extensions . . . . .	17
2.12	SPIR Version . . . . .	18
2.13	OpenCL Version . . . . .	18
2.14	memcpy functions . . . . .	19
2.15	Restrictions . . . . .	19
<b>3</b>	<b>SPIR and LLVM IR</b>	<b>19</b>
3.1	LLVM Triple . . . . .	19
3.2	LLVM Target data layout . . . . .	19
3.3	LLVM Supported Instructions . . . . .	19
3.4	LLVM Supported Intrinsic Functions . . . . .	21
3.5	SPIR ABI . . . . .	21
3.6	LLVM Linkage Types . . . . .	21
3.7	Calling Conventions . . . . .	22
3.8	Visibility Styles . . . . .	22
3.9	Parameter Attributes . . . . .	22
3.10	Garbage Collection Names . . . . .	22
3.11	Function Attributes . . . . .	23
3.12	Reserved identifiers . . . . .	23
3.13	Module Level Inline Assembly . . . . .	23
3.14	Pointer Aliasing Rules . . . . .	23
3.15	Volatile Memory Accesses . . . . .	23
3.16	Memory Model for Concurrent Operations . . . . .	23
3.17	Atomic Memory Ordering Constraints . . . . .	23
<b>A</b>	<b>SPIR name mangling</b>	<b>24</b>
A.1	Data types . . . . .	24
A.2	Type attributes . . . . .	25
A.3	The restrict qualifier . . . . .	26
A.4	Summary of changes . . . . .	26

## List of Tables

1	Mapping for built-in scalar data types . . . . .	7
2	Mapping for built-in vector types . . . . .	8
3	Mapping for other built-in data types . . . . .	8
4	sampler initialization values . . . . .	9
5	image channel data type values . . . . .	9
6	image channel order values . . . . .	10
7	Kernel Arg Info metadata description . . . . .	13
8	Mapping of type qualifiers . . . . .	14

9	Instructions, part 1 . . . . .	20
10	Instructions, part 2 . . . . .	21
11	Linkage types . . . . .	22
12	Parameter attributes . . . . .	22
13	Function attributes . . . . .	23
14	Mapping of OpenCL C builtin type names to mangled type names . . . . .	25
15	Mapping of OpenCL C type attributes to mangled names . . . . .	26

Copyright (c) 2011-2013 The Khronos Group Inc. All Rights Reserved.

This specification is protected by copyright laws and contains material proprietary to the Khronos Group, Inc. It or any components may not be reproduced, republished, distributed, transmitted, displayed, broadcast or otherwise exploited in any manner without the express prior written permission of Khronos Group. You may use this specification for implementing the functionality therein, without altering or removing any trademark, copyright or other notice from the specification, but the receipt or possession of this specification does not convey any rights to reproduce, disclose, or distribute its contents, or to manufacture, use, or sell anything that it may describe, in whole or in part.

Khronos Group grants express permission to any current Promoter, Contributor or Adopter member of Khronos to copy and redistribute UNMODIFIED versions of this specification in any fashion, provided that NO CHARGE is made for the specification and the latest available update of the specification for any version of the API is used whenever possible. Such distributed specification may be re-formatted AS LONG AS the contents of the specification are not changed in any way. The specification may be incorporated into a product that is sold as long as such product includes significant independent work developed by the seller. A link to the current version of this specification on the Khronos Group web-site should be included whenever possible with specification distributions.

Khronos Group makes no, and expressly disclaims any, representations or warranties, express or implied, regarding this specification, including, without limitation, any implied warranties of merchantability or fitness for a particular purpose or non-infringement of any intellectual property. Khronos Group makes no, and expressly disclaims any, warranties, express or implied, regarding the correctness, accuracy, completeness, timeliness, and reliability of the specification. Under no circumstances will the Khronos Group, or any of its Promoters, Contributors or Members or their respective partners, officers, directors, employees, agents or representatives be liable for any damages, whether direct, indirect, special or consequential damages for lost revenues, lost profits, or otherwise, arising from or in connection with these materials.

Khronos, StreamInput, WebGL, COLLADA, OpenKODE, OpenVG, OpenWF, OpenGL ES, OpenMAX, OpenMAX AL, OpenMAX IL and OpenMAX DL are trademarks and WebCL is a certification mark of the Khronos Group Inc. OpenCL is a trademark of Apple Inc. and OpenGL and OpenML are registered trademarks and the OpenGL ES and OpenGL SC logos are trademarks of Silicon Graphics International used under license by Khronos. All other product names, trademarks, and/or company names are used solely for identification and belong to their respective owners.

## Acknowledgements

**Editor:** Boaz Ouriel, Intel

**Contributors:**

- David Neto, Altera
- Anton Lokhmotov, ARM
- Mike Houston, AMD
- Micah Villmow, AMD
- Tanya Lattner, Apple
- Aaftab Munshi, Apple
- Holger Waechtler, Broadcom
- Andrew Richards, Codeplay
- Guy Benyei, Intel
- Javier E. Martinez, Intel
- Vinod Grover, NVIDIA
- Kedar Patil, NVIDIA
- Sumesh Udayakumaran, QUALCOMM
- Chihong Zhang, QUALCOMM
- Henry Styles, Xilinx
- Yaxun Liu, AMD
- Richard Relph, AMD
- Christopher Thomson-Walsh, Broadcom
- Dillon Sharlet, Intel

# 1 Introduction

This document defines version 1.2 of the OpenCL Standard Portable Intermediate Representation (SPIR). SPIR is a mapping from the OpenCL C programming language into LLVM IR.

This version of the specification is based on LLVM 3.2 [4] [3], and on OpenCL C as specified in the OpenCL 1.2 Specification [2].

The goal of SPIR is to provide a portable interchange format for partly compiled OpenCL C programs. The format:

- Is vendor neutral.
- Is not C source code.
- Supports almost all core features and KHR extensions for version 1.2 of OpenCL C. (A small number of features of OpenCL C are not expressible in SPIR.)
- Is designed to support vendor extensions.
- Is compact.
- Is designed to be efficiently loaded by an OpenCL implementation.
- Is designed to be useful as a target format for compilers of programming languages other than OpenCL C. This is a secondary goal of SPIR.

## 1.1 One format, two notations

LLVM IR has three semantically equivalent representations:

- An in-memory data structure manipulated by the LLVM software.
- A compact external binary representation, known as *bitcode* [3].<sup>2</sup>
- A human readable assembly language notation [4].

SPIR adopts two of these: the bitcode and assembly language notations from LLVM. For ease of exposition, the remainder of this document uses only the assembly language notation.

## 1.2 Name mangling

OpenCL C has many overloaded built-in functions, meaning the same function name is used with different argument and return types. For example, the `sin` built-in function is defined for both scalar and vector floating point argument and return types. SPIR distinguishes between all of the variations of the `sin` function by mangling the root name `sin` with its argument types.

This means that in SPIR all of the OpenCL C built-in functions are mangled based on their argument types.

Other kinds of names are not mangled in SPIR. In particular, regular and kernel user functions from OpenCL C are not mangled when mapped into SPIR.

By *not* mangling the names of regular functions, SPIR supports being the target for language families (other than C/C++) having their own distinctive type systems. In other words, mangling of user-level functions is beyond the scope of SPIR, and is subject to coordination among third parties (compiler front end and library implementors).

For names that do require mangling, SPIR adopts and extends the name mangling scheme from Section 5.1 of the Itanium C++ ABI [1]. Extensions are required to support OpenCL concepts absent from ordinary C++. The SPIR mangling scheme is defined in Appendix A.

---

<sup>2</sup>The LLVM 3.2 bitcode notation is only partly documented by [3]. However, bitcode notation is fully (but implicitly) defined by the behaviour of LLVM 3.2 software release.

## 2 OpenCL C mapping to SPIR

### 2.1 Supported Data Types

The following LLVM data types are supported:

#### 2.1.1 Built-in Scalar Data Types

Table 1 describes the mapping from the OpenCL C built-in scalar data types to SPIR built-in scalar data types.

OpenCL C Type	LLVM Type
bool	i1
char	i8
unsigned char, uchar	i8
short	i16
unsigned short, ushort	i16
int	i32
unsigned int, uint	i32
long	i64
unsigned long, ulong	i64
float	float
double	double
half	half
void	void

Table 1: Mapping for built-in scalar data types

Notes:

- Signed and unsigned values are sign extended or zero extended based on the deployed operation.
- While LLVM has many more primitive data types, only the ones described above are allowed in SPIR.

#### 2.1.2 Built-in Vector Types

Table 2 describes the mapping from the OpenCL C built-in vector data types to SPIR built-in scalar data types. Supported values of  $n$  are 2, 3, 4, 8, and 16 for all vector data types.

OpenCL C Type	LLVM Type
<i>charn</i>	< n x i8 >
<i>ucharn</i>	< n x i8 >
<i>shortn</i>	< n x i16 >
<i>ushortn</i>	< n x i16 >
<i>intn</i>	< n x i32 >
<i>uintn</i>	< n x i32 >
<i>longn</i>	< n x i64 >
<i>ulongn</i>	< n x i64 >
<i>halfn</i>	< n x half >
<i>floatn</i>	< n x float >
<i>doublen</i>	< n x double >

Table 2: Mapping for built-in vector types

Note: LLVM supports many more vector data types, however only the ones described above are allowed in SPIR. Specifically, a vector of `i1`'s is disallowed in SPIR.

### 2.1.3 Other Built-in Data Types

Table 3 defines the mapping of OpenCL images, sampler, events, `size_t`, `ptrdiff_t`, `uintptr_t`, `intptr_t` data types to LLVM data types

OpenCL C Type	LLVM Type	LLVM Name
<code>image1d_t</code>	opaque*	<code>%opencl.image1d_t</code>
<code>image1d_array_t</code>	opaque*	<code>%opencl.image1d_array_t</code>
<code>image1d_buffer_t</code>	opaque*	<code>%opencl.image1d_buffer_t</code>
<code>image2d_t</code>	opaque*	<code>%opencl.image2d_t</code>
<code>image2d_array_t</code>	opaque*	<code>%opencl.image2d_array_t</code>
<code>image3d_t</code>	opaque*	<code>%opencl.image3d_t</code>
<code>image2d_msaa_t</code>	opaque*	<code>%opencl.image2d_msaa_t</code>
<code>image2d_array_msaa_t</code>	opaque*	<code>%opencl.image2d_array_msaa_t</code>
<code>image2d_msaa_depth_t</code>	opaque*	<code>%opencl.image2d_msaa_depth_t</code>
<code>image2d_array_msaa_depth_t</code>	opaque*	<code>%opencl.image2d_array_msaa_depth_t</code>
<code>image2d_depth_t</code>	opaque*	<code>%opencl.image2d_depth_t</code>
<code>image2d_array_depth_t</code>	opaque*	<code>%opencl.image2d_array_depth_t</code>
<code>event_t</code>	opaque*	<code>%opencl.event_t</code>
<code>sampler_t</code>	<code>i32</code>	N/A
<code>size_t</code>	<code>i32</code> or <code>i64</code>	N/A
<code>ptrdiff_t</code>	<code>i32</code> or <code>i64</code>	N/A
<code>uintptr_t</code>	<code>i32</code> or <code>i64</code>	N/A
<code>intptr_t</code>	<code>i32</code> or <code>i64</code>	N/A

Table 3: Mapping for other built-in data types

Notes:

- The names given to opaque data types are reserved for SPIR and shall not be used otherwise.



- The OpenCL `size_t`, `ptrdiff_t`, `uintptr_t` and `intptr_t` data types are mapped to LLVM `i32` when the device address width is equal to 32 bits and to LLVM `i64` when the device address width is equal 64 bits

### 2.1.3.1 Declaring sampler variables

A sampler variable is an `i32` constant-qualified module scope variable in the constant address space, initialized with an `i32` constant value. The `i32` constant value is interpreted as a bit-field specifying the following properties:

Sampler State	Init Values
addressing mode	CLK_ADDRESS_NONE=0 CLK_ADDRESS_CLAMP=1 CLK_ADDRESS_CLAMP_TO_EDGE=2 CLK_ADDRESS_REPEAT=3 CLK_ADDRESS_MIRRORED_REPEAT=4
normalized coords	CLK_NORMALIZED_COORDS_FALSE=0 CLK_NORMALIZED_COORDS_TRUE=8
filter mode	CLK_FILTER_NEAREST=0 CLK_FILTER_LINEAR=16

Table 4: sampler initialization values

### 2.1.3.2 Image channel data type values

The `get_image_channel_data_type()` built-in returns an integer value which represents the image channel data type. The following table indicates the valid values:

Channel order	Value
CLK_SNORM_INT8	0
CLK_SNORM_INT16	1
CLK_UNORM_INT8	2
CLK_UNORM_INT16	3
CLK_UNORM_SHORT_565	4
CLK_UNORM_SHORT_555	5
CLK_UNORM_SHORT_101010	6
CLK_SIGNED_INT8	7
CLK_SIGNED_INT16	8
CLK_SIGNED_INT32	9
CLK_UNSIGNED_INT8	10
CLK_UNSIGNED_INT16	11
CLK_UNSIGNED_INT32	12
CLK_HALF_FLOAT	13
CLK_FLOAT	14
CLK_UNORM_INT24	15

Table 5: image channel data type values

### 2.1.3.3 Image channel order values

The `get_image_channel_order()` built-in returns an integer value which represents the image channel order. The following table indicates the valid values:

Channel order	Value
CLK_A	0
CLK_R	1
CLK_Rx	2
CLK_RG	3
CLK_RGx	4
CLK_RA	5
CLK_RGB	6
CLK_RGBx	7
CLK_RGBA	8
CLK_ARGB	9
CLK_BGRA	10
CLK_INTENSITY	11
CLK_LUMINANCE	12
CLK_DEPTH	13
CLK_DEPTH_STENCIL	14

Table 6: image channel order values

### 2.1.3.4 Zero events

Zero events are represented using the LLVM `null` keyword.

### 2.1.3.5 NULL pointer

NULL pointers are represented using the LLVM `null` keyword.

## 2.1.4 Alignment of Types

SPIR follows the alignment rules of OpenCL. Therefore:

- Stack allocations and module scope variable declarations must follow the alignment rules defined in OpenCL specification.
- All `load` and `store` operations need to be aligned.

### 2.1.5 Structs

The alignment of structures data members is the alignment of the SPIR data type. Extra padding is disallowed. The alignment of the structure is the alignment of the member which requires the largest alignment.

When mapping an OpenCL C struct data type to SPIR, the order of members shall be preserved.

## 2.2 Address space qualifiers

OpenCL C address spaces are mapped to the LLVM `addrspace(n)` qualifier using the following convention:

- 0 – private
- 1 – global
- 2 – constant
- 3 – local

Note: Casts between address spaces is disallowed in SPIR.

Note: Each OpenCL C function-scope local variable is mapped into an LLVM module-level variable in address space 3. They are not allocated using `alloca` instruction. The name of the module-level variable consists of the function name, followed by a period, followed by the source identifier.

Example OpenCL C program:

```
void foo(void) {
    local float4 lf4;
}
```

A valid SPIR mapping:

```
; Unmangled component names shown here.
; float4 must be 16 bytes aligned.
@foo.lf4 = internal addrspace(3) global <4 x float> zeroinitializer, align 16

define spir_kernel void @foo() nounwind {
entry:
    ret void
}
```

In OpenCL C, a kernel function can call another kernel. However, when the called kernel declares a variable in the `__local` address space, then the behaviour is implementation defined. SPIR supports a kernel calling another kernel, but does not allow the called kernel to have a variable in the `__local` address space. For example, the following example is not valid SPIR:

```
@bar.lf4 = internal addrspace(3) global <4 x float> zeroinitializer, align 16

define spir_kernel void @bar() nounwind {
entry:
    ret void
}

define spir_kernel void @callbar() nounwind {
entry:
    call spir_kernel void @bar() ; This is not supported by SPIR
    ret void
}
```

## 2.3 Kernel qualifiers

Adding qualifiers and attributes to a kernel and its arguments is achieved by usage of the LLVM metadata infrastructure. Each SPIR module has a `opengl.kernels` named metadata node containing a list of metadata objects. Each metadata object in `opengl.kernels` references a list of

metadata objects, each of which represents a single kernel. The first value in a SPIR function metadata object is the SPIR function that represents an OpenCL kernel. The rest of the metadata objects are additional attributes and information which is attached to the SPIR function. The description of each metadata object inside the SPIR function metadata list is described in the other sections.

The following LLVM textual representation shows how SPIR function attributes are represented:

```
!openc1.kernels = !{ !0,!1,...,!N }
; Note: The first element is always an LLVM::Function signature
!0 = metadata !{ <function signature>, !01, !02, ..., , !0i }
!1 = metadata !{ <function signature>, !11, !12, ..., , !1j }
...
!N = metadata !{ <function signature>, !N1, !N2, ..., , !Nk }
```

### 2.3.1 Optional attribute qualifiers

#### 2.3.1.1 Work group size information

Attaching `work_group_size_hint` and `reqd_work_group_size` information to kernels is achieved using LLVM metadata infrastructure. Two new metadata object are introduced. The first item in the metadata object is the string `"work_group_size_hint"` or `"reqd_work_group_size"` followed by three `i32` constant values. The three `i32` values specify the (X,Y,Z) group dimensions.

```
; work_group_size_hint(128,1,1)
!0 = metadata !{ metadata !"work_group_size_hint", i32 128, i32 1, i32 1}
; reqd_work_group_size(128,1,1)
!1 = metadata !{ metadata !"reqd_work_group_size", i32 128, i32 1, i32 1}
```

Note:

- Attaching the work group size hint to a non-kernel SPIR function is invalid.

#### 2.3.1.2 Vector type hint information

Attaching `vec_type_hint` information to kernels is achieved using LLVM metadata infrastructure. The first argument in each metadata object is the string `"vec_type_hint"` followed by a typed `undef` LLVM value and an additional `i1` value representing the signedness of the value.

```
; vec_type_hint(float)
!0 = metadata !{ metadata !"vec_type_hint", float undef, i1 1}
; vec_type_hint(uint8)
!1 = metadata !{ metadata !"vec_type_hint", <8 x i32> undef, i1 0}
...
; vec_type_hint(<type>)
!H = metadata !{ metadata !"vec_type_hint", <type> undef, i1 isSigned}
```

Note:

- Attaching vector type hint information to a non-kernel SPIR function is invalid.
- The `double` data type is an optional type and using it requires marking the SPIR module as using the `cl_doubles` optional core feature. See Section 2.11.1.

## 2.4 Kernel Arg Info

Kernel argument specific information is preserved using metadata objects. These objects are generated for every kernel, with an exception for the `kernel_arg_name` metadata, which is generated only when the `-cl-kernel-arg-info` build option is specified for compilation. The metadata nodes describing the kernel argument info are in the form of a string tag, and then a list of the corresponding data for each one of the kernel's arguments.

The following table shows the valid kernel argument information types and values:

ARG Info	Type	Values
"kernel_arg_address_space"	i32	0 – private 1 – global 2 – constant 3 – local
"kernel_arg_access_qual"	string metadata	"read_only" "write_only" "read_write" "none"
"kernel_arg_type"	string metadata	The type name specified for the argument. The type name returned will be the argument type name as it was declared with any whitespace removed. If argument type name is an unsigned scalar type (i.e. unsigned char, unsigned short, unsigned int, unsigned long), uchar, ushort, uint and ulong will be returned. The argument type name returned does not include any type qualifiers.
"kernel_arg_type_qual"	string metadata	"const" "restrict" "volatile" or a single space separated combination of these.
"kernel_arg_name"	string metadata	the name specified for the argument. Generated only when the <code>-cl-kernel-arg-info</code> build option is specified for compilation.

Table 7: Kernel Arg Info metadata description

Example:

```
__kernel void helloworld(__global char* in, __global char* out);

!opencl.kernels = !{!0}

!0 = metadata !{void (i8 addrspace(1)*, i8 addrspace(1))* @helloworld, metadata !1,
               metadata !2, metadata !3, metadata !4, metadata !5}
!1 = metadata !{metadata !"kernel_arg_address_space", i32 1, i32 1}
!2 = metadata !{metadata !"kernel_arg_access_qual", metadata !"none", metadata !"none"}
!3 = metadata !{metadata !"kernel_arg_type", metadata !"char*", metadata !"char*"}
!4 = metadata !{metadata !"kernel_arg_type_qual", metadata !"", metadata !""}
!5 = metadata !{metadata !"kernel_arg_name", metadata !"in", metadata !"out"}
```

## 2.5 Storage class specifier

The OpenCL C `extern` and `static` storage class specifiers map to the LLVM `external` and `internal` linkage types, respectively.

## 2.6 Type qualifiers

OpenCL C Type Qualifier	LLVM Mapping
<code>const</code>	<code>constant</code>
<code>restrict</code>	<code>noalias</code>
<code>volatile</code>	Certain memory accesses, such as loads, stores, and spir memcpys may be marked volatile. (See Notes below.)

Table 8: Mapping of type qualifiers

Notes for the `volatile` qualifier:

1. The optimizers must not change the number of volatile operations or change their order of execution relative to other volatile operations.
2. The optimizers may change the order of volatile operations relative to non-volatile operations.

## 2.7 Attribute Qualifiers

### 2.7.1 Type Attributes

SPIR provides structure types to describe unions and structures. The layout of structures in SPIR must take into consideration the alignment rules of OpenCL C. Optimizers are not allowed to do any modifications to structures.

#### 2.7.1.1 aligned attribute

SPIR structures can be aligned at declaration time. This applies both to module level structures and stack allocations using the `alloca` instruction.

#### 2.7.1.2 packed attribute

SPIR structures are marked as packed when `__attribute__((packed))` is used in OpenCL C.

Example:

`<{i8 , i32}>` is a packed structure known to be 5 bytes in size.

### 2.7.2 Variable Attributes

#### 2.7.2.1 aligned attribute

- SPIR variables can be aligned at declaration time. This applies both to module level variables and stack allocations using the `alloca` instruction.

- SPIR does not provide a mechanism to reflect the alignment of structure members. Instead the SPIR generator is expected to create a structure definition taking into consideration this attribute, for example by inserting dummy members to occupy the extra space. Optimizers are not allowed to modify the data layout of structures.

## 2.8 Compiler Options

Compiler options are represented in SPIR using a named metadata node `opencl.compiler.options`. The named metadata node will contain a single metadata node that holds a list of string metadata objects. Each string metadata object corresponds to a single standard OpenCL compiler option. Preprocessor options are not saved in SPIR and the list of the allowed options are as follows:

- `-cl-single-precision-constant`
- `-cl-denorms-are-zero`
- `-cl-fp32-correctly-rounded-divide-sqrt`
- `-cl-opt-disable`
- `-cl-mad-enable`
- `-cl-no-signed-zeros`
- `-cl-unsafe-math-optimizations`
- `-cl-finite-math-only`
- `-cl-fast-relaxed-math`
- `-w`
- `-Werror`
- `-cl-kernel-arg-info`
- `-create-library`
- `-enable-link-options`

Note: The `-cl-std` option is propagated to the `opencl.ocl.version` as defined in Section 2.13, OpenCL Version.

This example indicates that both `-cl-mad-enable` and `-cl-denorms-are-zero` standard compile options were used to compile the module:

```
!opencl.compiler.options = !{!2}
!2 = metadata !{metadata !"-cl-mad-enable", metadata !"-cl-denorms-are-zero"}
```

Compilation options which are not part of the OpenCL specification are stored via the named metadata node `opencl.compiler.ext.options`. The named metadata node contains a single metadata node that holds a list of string metadata objects. Each string metadata object corresponds to a non-standard compile option. Compilation options which appear in `opencl.compiler.ext.options` shall not affect functional portability of the SPIR module.

This example indicates that the (hypothetical) non-standard option `-opt-arch-pdp11` was used to compile the module:

```
!opencl.compiler.ext.options = !{!5}
!5 = metadata !{metadata !"-opt-arch-pdp11"}
```

## 2.9 Preprocessor Directives and Macros

### 2.9.1 Preprocessor Directives

The named metadata `opencl.enable.FP_CONTRACT` can be used to enable contractions at module level. If the named metadata node exists contractions can be generated by a SPIR optimizer at module level.

Note: This is one case where some valid OpenCL C programs are not expressible in SPIR. OpenCL C permits control over the `FP_CONTRACT` pragma at a granular level: at various points in program scope, and within functions. In contrast, SPIR only supports a single module-wide setting.

### 2.9.2 Macros

It is the SPIR generator's responsibility to deal with the following macros:

- Replace user macros
- Replace `__FILE__` with a character string literal
- Replace `__LINE__` with an i32 constant
- Replace `CL_VERSION_1_0` with the i32 constant 100
- Replace `CL_VERSION_1_1` with the i32 constant 110
- Replace `CL_VERSION_1_2` with the i32 constant 120
- Replace `CL_VERSION_2_0` with the i32 constant 200
- Replace `__OPENCL_C_VERSION__` with the i32 constant described in `-cl-std` build option. If the `-cl-std` build option is not specified the behavior of this Macro follows the `__OPENCL_VERSION__` rules.
- Replace `__OPENCL_VERSION__` with call to the new i32 `__spir_opengl_version()` builtin function which exposes the OpenCL "C" version supported by the device. The return value of this function is 100, 110, or 120 for OpenCL version 1.0, 1.1 and 1.2 (respectively).
- Replace `__IMAGE_SUPPORT__` with a call to the new i32 `__spir_image_support()` builtin function which is used to determine if the OpenCL device supports images. The return value of this function is 1 if the device supports images and is undefined otherwise.
- Replace `__FAST_RELAXED_MATH__` with an i32 constant 1 if the `-cl-fast-relaxed-math` build option is used.

Note: The builtin functions described in this subsection are shown with their unmangled names.

## 2.10 Built-ins

### 2.10.1 Name Mangling

All of the built-in names described in this document are shown in their unmangled form.

### 2.10.2 Synchronization Functions

Synchronization functions accept `cl_mem_fence_flags` enumeration as an argument. In SPIR this maps to a constant i32 value which is a bitwise OR between `CLK_LOCAL_MEM_FENCE = 1` and `CLK_GLOBAL_MEM_FENCE = 2`.

Note: The legal values are 1, 2, and 3



### 2.10.3 The printf function

The `printf` function is supported, and is mangled according to its prototype as follows:

```
int printf(constant char * restrict fmt, ... )
```

Note that the ellipsis formal argument (...) is mangled to argument type specifier `z`.

In SPIR the conversion specifiers `e,E,g,G,a,A` require a double type argument to be passed to the function `printf`. Thus a `float` or `half` argument that is a scalar type should be explicitly converted to a `double`. A device that doesn't support the `double` data type shall disregard this explicit conversion, or replace the conversion with a conversion to a `float` data type in the case of a `half` data type argument.

The presence of this conversion alone is not enough to force the listing of `"cl_doubles"` as a "used optional core features" for this SPIR instance.

## 2.11 KHR Extensions

### 2.11.1 Declaration of used optional core features

The named metadata object `opengl.used.optional.core.features` contains a single metadata object. The metadata object should contain a list of metadata strings, each of which encodes the name of an optional core feature used by the SPIR module.

This is the list of valid strings and their meaning:

- `"cl_images"` - indicates that images are used
- `"cl_doubles"` - indicates that doubles are used

A device may reject a SPIR module using an unsupported optional core feature. This example indicates that the module uses both images and doubles.

```
!opengl.used.optional.core.features = !{!0}
!0 = metadata !{metadata !"cl_doubles", metadata !"cl_images"}
```

### 2.11.2 Declaration of used KHR extensions

A SPIR module using one or more KHR extension, must declare them inside the SPIR module. The named metadata object `opengl.used.extensions` is used to declare this list. The named metadata object contains a metadata object consisting of a list of metadata strings, where each string indicates a usage of a KHR extension inside the SPIR module.

This is the list of extension strings:

- `cl_khr_int64_base_atomics`
- `cl_khr_int64_extended_atomics`
- `cl_khr_fp16`
- `cl_khr_gl_sharing`
- `cl_khr_gl_event`
- `cl_khr_d3d10_sharing`
- `cl_khr_media_sharing`
- `cl_khr_d3d11_sharing`

- `cl_khr_global_int32_base_atomics`
- `cl_khr_global_int32_extended_atomics`
- `cl_khr_local_int32_base_atomics`
- `cl_khr_local_int32_extended_atomics`
- `cl_khr_byte_addressable_store`
- `cl_khr_3d_image_writes`
- `cl_khr_gl_msaa_sharing`
- `cl_khr_depth_images`
- `cl_khr_gl_depth_images`

This example shows that `cl_khr_fp16` and `cl_khr_int64_base_atomics` standard extensions are used in the module.

```
!openc1.used.extensions = !{!6}
!6 = metadata !{metadata !"cl_khr_fp16", metadata !"cl_khr_int64_base_atomics"}
```

Notes:

- A device may reject a SPIR module using an unsupported KHR extension.
- A device using `cl_khr_3d_image_writes` must also declare its use of `cl_images` inside `openc1.used.optional.core.features`.
- `cl_khr_fp64` doesn't exist in SPIR. Instead SPIR generators should use the `cl_doubles` optional core features.

## 2.12 SPIR Version

The SPIR version used by the module is stored in the `openc1.spir.version` named metadata. The named metadata contains a metadata node consisting of a list of two `i32` constant values denoting the major and minor version numbers.

The following example indicates the module uses SPIR version 1.2:

```
!openc1.spir.version = !{!3}
!3 = metadata !{i32 1, i32 2}
```

## 2.13 OpenCL Version

The OpenCL version used by the module is stored in the `openc1.ocl.version` named metadata node. The named metadata node contains a metadata node consisting of a list of two `i32` constant values denoting the major and minor version numbers.

This example indicates the module is compiled for OpenCL 1.0:

```
!openc1.ocl.version = !{!4}
!4 = metadata !{i32 1, i32 0}
```

This example indicates the module is compiled for OpenCL 1.1:

```
!openc1.ocl.version = !{!4}
!4 = metadata !{i32 1, i32 1}
```

## 2.14 memcpy functions

The usage of LLVM memcpy intrinsics is allowed in SPIR.

## 2.15 Restrictions

Restrictions from OpenCL C also apply to programs represented in SPIR.

Also, recall that use of FP\_CONTRACT is encoded at the module level. See Section 2.9.1 for a discussion of how this limits what OpenCL programs may be represented in SPIR.

# 3 SPIR and LLVM IR

## 3.1 LLVM Triple

SPIR introduces a couple of new LLVM triples called “spir-unknown-unknown” and “spir64-unknown-unknown”

```
target triple = "spir-unknown-unknown"
target triple = "spir64-unknown-unknown"
```

“spir” targets devices with address width of 32 bits. “spir64” targets devices with address width of 64 bits.

## 3.2 LLVM Target data layout

The spir triple datalayout is as follows:

```
target datalayout = "e-p:32:32:32-i1:8:8-i8:8:8-i16:16:16-i32:32:32-i64:64:64-
f32:32:32-f64:64:64-v16:16:16-v24:32:32-v32:32:32-v48:64:64-
v64:64:64-v96:128:128-v128:128:128-v192:256:256-v256:256:256-
v512:512:512-v1024:1024:1024"
```

The spir64 triple datalayout is as follows:

```
target datalayout = "e-p:64:64:64-i1:8:8-i8:8:8-i16:16:16-i32:32:32-i64:64:64-
f32:32:32-f64:64:64-v16:16:16-v24:32:32-v32:32:32-v48:64:64-
v64:64:64-v96:128:128-v128:128:128-v192:256:256-v256:256:256-
v512:512:512-v1024:1024:1024"
```

## 3.3 LLVM Supported Instructions

The following tables show which LLVM instructions are may be used in SPIR:

LLVM Instruction Family	Instruction name	Supported
Terminator	ret	yes
Terminator	br	yes
Terminator	switch	yes
Terminator	indirectbr	no, required for GNU extension (array of pointer of functions)
Terminator	invoke	no, exception handling related
Terminator	unwind	no, exception handling related
Terminator	resume	no, exception handling related
Terminator	unreachable	yes, might be used for switch statements
Binary	add	yes
Binary	fadd	yes
Binary	sub	yes
Binary	fsub	yes
Binary	mul	yes
Binary	fmul	yes
Binary	udiv	yes
Binary	sdiv	yes
Binary	fdiv	yes
Binary	urem	yes
Binary	srem	yes
Binary	frem	yes
Bitwise Binary	shl	yes, left-shifted by $\log_2(N)$ , where N is the number of bits used to represent the data type of the shifted value
Bitwise Binary	lshr	yes, right-shifted by $\log_2(N)$ , where N is the number of bits used to represent the data type of the shifted value.
Bitwise Binary	ashr	yes, right-shifted by $\log_2(N)$ , where N is the number of bits used to represent the data type of the shifted value. <b>exact</b> is disallowed and used for trap values
Bitwise Binary	and	yes
Bitwise Binary	or	yes
Bitwise Binary	xor	yes
Vector	extractelement	yes
Vector	insertelement	yes
Vector	shufflevector	yes
Aggregate	extractvalue	yes
Aggregate	insertvalue	yes
Memory Access & Addressing	alloca	yes
Memory Access & Addressing	load	yes, <b>atomic</b> is disallowed
Memory Access & Addressing	store	yes, <b>atomic</b> is disallowed
Memory Access & Addressing	fence	no, use built-ins instead
Memory Access & Addressing	cmpxchg	no, use built-ins instead
Memory Access & Addressing	atomicrmw	no, use built-ins instead
Memory Access & Addressing	getelementptr	yes

Table 9: Instructions, part 1

LLVM Instruction Family	Instruction name	Supported
Conversion Operations	trunc .. to	yes, but only for scalars
Conversion Operations	zext .. to	yes, but only for scalars
Conversion Operations	sext .. to	yes, but only for scalars
Conversion Operations	fptrunc .. to	yes, but only for scalars
Conversion Operations	fpext .. to	yes, but only for scalars
Conversion Operations	fptoui .. to	yes, but only for scalars
Conversion Operations	fptosi .. to	yes, but only for scalars
Conversion Operations	uitofp .. to	yes, but only for scalars
Conversion Operations	sitofp .. to	yes, but only for scalars
Conversion Operations	ptrtoint .. to	no, use size_t intrinsics instead
Conversion Operations	inttoptr .. to	no, use size_t intrinsics instead
Conversion Operations	bitcast .. to	yes
Other Operations	icmp	yes
Other Operations	fcmp	yes
Other Operations	phi	yes
Other Operations	select	yes
Other Operations	call	yes, but not to pointers to functions
Other Operations	va_arg	no, not supported by OpenCL
Other Operations	landingpad_arg	no

Table 10: Instructions, part 2

### 3.4 LLVM Supported Intrinsic Functions

None of the LLVM intrinsics are allowed in SPIR except the memcpy intrinsics.

### 3.5 SPIR ABI

In this section we define the application binary interface for OpenCL "C" programs in SPIR. The SPIR ABI defines the interfaces between the SPIR program and the OpenCL runtime, built-ins libraries and additional third party SPIR libraries.

Each function argument and return type is classified as follows:

- Any aggregate type is passed as a pointer. Memory allocation (if needed) is the responsibility of the caller function.
- Enumeration types are handled as the underlying integer type.
- If the argument type is a promotable integer type, it will be extended according to the C99 integer promotion rules.
- Any other type, including floating point types, vectors, etc.. will be passed directly as the corresponding LLVM type.

Note: The ABI described in this section is implemented in Clang 3.2 and is called the "default" ABI.

### 3.6 LLVM Linkage Types

The following table shows the LLVM linkage types allowed in SPIR:

Linkage type	Supported
private	yes
linker_private	no
linker_private_weak	no
linker_private_weak_def_auto	no
available_externally	yes (describes C99 inline definition)
linkonce	no
internal	yes (maps to static)
weak	no
common	yes
appending	no
extern_weak	no
linkonce_odr	no
weak_odr	no
external	yes (will be required for libraries)
dllimport	no
dllexport	no

Table 11: Linkage types

### 3.7 Calling Conventions

SPIR kernels should use "spir\_kernel" calling convention. Non-kernel functions use "spir\_func" calling convention. All other calling conventions are disallowed.

### 3.8 Visibility Styles

Visibility styles are not used in SPIR and should be set to "default". Other values are disallowed.

### 3.9 Parameter Attributes

The following table defines which parameter attributes are usable in SPIR:

Parameter Attribute	Supported
zeroext	yes
signext	yes
inreg	no
byval	yes
sret	yes
nocapture	yes
nest	no

Table 12: Parameter attributes

### 3.10 Garbage Collection Names

Garbage collection is not part of SPIR, hence functions are not allowed to specify a garbage collector name.

### 3.11 Function Attributes

Every SPIR function should use the `nounwind` attribute. In addition the following optional attributes could be used: `alwaysinline`, `inlinehint`, `noinline`, `readnone`, `readonly`. The rest of the function attributes are disallowed.

Function Attribute	Supported
<code>alignstack</code>	no
<code>alwaysinline</code>	yes
<code>nonlazybind</code>	no
<code>inlinehint</code>	yes
<code>naked</code>	no
<code>noimplicitfloat</code>	no
<code>noinline</code>	yes
<code>noredzone</code>	no
<code>noreturn</code>	no
<code>nounwind</code>	yes, needs to be always set
<code>optsize</code>	no
<code>readnone</code>	yes
<code>readonly</code>	yes
<code>ssp</code>	no
<code>sspreq</code>	no
<code>uwtable</code>	no
<code>returns_twice</code>	no

Table 13: Function attributes

### 3.12 Reserved identifiers

All identifiers that begin with `opencl.*` are reserved and shall not be used by SPIR generators (for user source identifiers).

### 3.13 Module Level Inline Assembly

LLVM module level inline assembly is not allowed in SPIR.

### 3.14 Pointer Aliasing Rules

SPIR follows the pointer aliasing rules of LLVM.

### 3.15 Volatile Memory Accesses

SPIR requires use of volatile memory accesses and follows LLVM IR rules for `load`'s, `store`'s and `llvm.memcpy`'s.

### 3.16 Memory Model for Concurrent Operations

SPIR does not use the LLVM atomic intrinsics, because OpenCL has its own set of intrinsics.

### 3.17 Atomic Memory Ordering Constraints

The LLVM atomic orderings are disallowed in SPIR.

## A SPIR name mangling

In order to support cross device compatibility of SPIR, the name mangling scheme must be standardized across vendors. SPIR adopts and extends the name mangling scheme in Section 5.1 of the Itanium C++ ABI [1]. There are three major issues to deal with, along with many minor items. The major items are data types, address spaces, and overloaded 'C' functions.

Normally, 'C' functions require no overloading, and their names are not mangled. When generating SPIR, OpenCL C built-in functions must use this mangling scheme.

### A.1 Data types

The following table shows the mapping from OpenCL C data types to the type names used in the mangling scheme:



OpenCL C type	Mangling scheme type name
bool	b
unsigned char, char	h
char	c
unsigned short, short	t
short	s
unsigned int, uint	j
int	i
unsigned long, ulong	m
long	l
half	Dh
float	f
double	d
pointer to private address space	P< <i>mangled-element-type-name</i> >
pointer to non private address space	PU3ASN< <i>mangled-element-type-name</i> > (where N is the address space number)
<i>Vector types with N elements</i>	DvN_< <i>mangled-element-type-name</i> > (where N is one of 2, 3, 4, 8, 16)
image1d_t	11ocl_image1d
image1d_array_t	16ocl_image1darray
image1d_buffer_t	17ocl_image1dbuffer
image2d_t	11ocl_image2d
image2d_array_t	16ocl_image2darray
image3d_t	11ocl_image3d
image2d_msaa_t	15ocl_image2dmsaa
image2d_array_msaa_t	20ocl_image2darraymsaa
image2d_msaa_depth_t	20ocl_image2dmsaaadepth
image2d_array_msaa_depth_t	25ocl_image2darraymsaaadepth
image2d_depth_t	16ocl_image2ddepth
image2d_array_depth_t	21ocl_image2darraydepth
event_t	9ocl_event
sampler_t	11ocl_sampler
size_t, uintptr_t	treated as uint or ulong
ptrdiff_t, intptr_t	treated as int or long

Table 14: Mapping of OpenCL C builtin type names to mangled type names

## A.2 Type attributes

The following table shows the mapping from OpenCL C specific type qualifiers to their mangled encoding:

OpenCL C type attribute	Mangled encoding
read_only	U1R
write_only	U1W
read_write (Reserved)	U1B
LLVM address space $N$	U2AN

Table 15: Mapping of OpenCL C type attributes to mangled names

### A.3 The restrict qualifier

The Itanium ABI states:

The restrict qualifier is part of the C99 standard, but is strictly an extension to C++ at this time. There is no standard specification of whether the restrict attribute is part of the type for overloading purposes. An implementation should include its encoding in the mangled name if and only if it also treats it as a distinguishing attribute for overloading purposes. This ABI does not specify that choice.”

SPIR encodes the “restrict” qualifier as part of the mangled name using the ‘r’ token in the CV-qualifiers. Hence SPIR treats the “restrict” qualifier as significant for overloading.

### A.4 Summary of changes

The following is a summary of the mangling of builtin types:

```

<builtin-type> ::= v # void (Maps to OpenCL void)
                ::= w # wchar_t (*Not valid)
                ::= b # bool (Maps to OpenCL bool)
                ::= c # char (Maps to OpenCL char)
                ::= a # signed char (*Not valid)
                ::= h # unsigned char (Maps to OpenCL uchar)
                ::= s # short (Maps to OpenCL short)
                ::= t # unsigned short (Maps to OpenCL ushort)
                ::= i # int (Maps to OpenCL int)
                ::= j # unsigned int (Maps to OpenCL uint)
                ::= l # long (Maps to OpenCL long)
                ::= m # unsigned long (Maps to OpenCL ulong)
                ::= x # long long, __int64 (*Not valid)
                ::= y # unsigned long long, __int64 (*Not valid)
                ::= n # __int128 (*Not valid)
                ::= o # unsigned __int128 (*Not valid)
                ::= f # float (Maps to OpenCL float)
                ::= d # double (Maps to OpenCL double)
                ::= e # long double, __float80 (*Not valid)
                ::= g # __float128 (*Not valid)
                ::= z # ellipsis (*Valid only for printf*)
                ::= Dd # IEEE 754r decimal floating point (64 bits) (*Not valid)
                ::= De # IEEE 754r decimal floating point (128 bits) (*Not valid)
                ::= Df # IEEE 754r decimal floating point (32 bits) (*Not valid)
                ::= Dh # IEEE 754r half-precision floating point (16 bits) (Maps to OpenCL Half)
                ::= Di # char32_t (*Not valid)
                ::= Ds # char16_t (*Not valid)
                ::= Da # auto (in dependent new-expressions)
                ::= Dn # std::nullptr_t (i.e., decltype(nullptr))

```

```

::= P<builtin-type> # A pointer to private address space.
::= PU3ASN<builtin-type> # A pointer to address space 'N' (non-private).
    # Only values of 1, 2 and 3 are valid.
::= DvN_<builtin-type> # An OpenCL vector of length 'N' of the specified type.
    # Only values of 2, 3, 4, 8 and 16 are valid.
::= 11ocl_image1d # A 1d image type
::= 16ocl_image1darray # A 1d image array type
::= 17ocl_image1dbuffer # A 1d image buffer type
::= 11ocl_image2d # A 2d image type
::= 16ocl_image2darray # A 2d image array type
::= 11ocl_image3d # A 3d image type
::= 15ocl_image2dmsaa
::= 20ocl_image2darraymsaa
::= 20ocl_image2dmsaadepth
::= 25ocl_image2darraymsaadepth
::= 16ocl_image2ddepth
::= 21ocl_image2darraydepth
::= 9ocl_event # A event type
::= 11ocl_sampler # A sampler type
::= u <source-name> # vendor extended type

```

SPIR also extends the CV-qualifier list as follows. All CV-qualifiers are order-insensitive.

```

<CV-qualifiers> ::= [r] [V] [K] # restrict (C99), volatile, const
                ::= [U1W] [U1B] [U1R] # write_only, read_write("both"; Reserved), read_only
                ::= [U2A[N]] # Address space N, where N is valid for 1-5.
                # These are order-insensitive.

```

Note: By default, objects reside in the `private` address space (number 0). No address space qualification is used to indicate the private address space.

## References

- [1] CodeSourcery, Compaq, EDG, HP, IBM, Intel, Red Hat, SGI, and others. Itanium C++ ABI. <http://mentorembedded.github.com/cxx-abi/abi.html>.
- [2] Khronos OpenCL Working Group. The OpenCL Specification, version 1.2. <http://www.khronos.org/registry/cl/specs/ocl-1.2.pdf>, November 2012.
- [3] LLVM Team. LLVM Bitcode File Format. <http://www.llvm.org/releases/3.2/docs/BitCodeFormat.html>, 2012. Version 3.1.
- [4] LLVM Team. LLVM Language Reference Manual. <http://www.llvm.org/releases/3.2/docs/LangRef.html>, 2012. Version 3.1.